## 3.5 HP

Engine Model (Color) Engine Type Bore x Stroke - in (mm) Displacement - cu in (cc) Gear Ratio Full Throttle RPM Range Weight - lbs (kg)* Starting Controls Fuel Induction Steering Trim Method Shaft Length - in (mm) Dil Tank Capacity - fl oz (ml) Recommended Fuel Warranty Emissions Compliance Warranty Emissions Compliance EPA 2013 / CARB 3 STAR / European Union		
Bore x Stroke - in (mm)  Displacement - cu in (cc)  Gear Ratio  Full Throttle RPM Range  Weight - lbs (kg)*  Starting  Controls  Fuel Induction  Steering  Trim Method  Shaft Length - in (mm)  Dill Tank Capacity - fl oz (ml)  Recommended Gil  Recommended Fuel  Warranty  Emissions Compliance  Warranty  2.17 x 1.42 (55 x 36)  5.2 (86)  5.2 (86)  5.2 (86)  5.2 (86)  5.2 (86)  5.2 (86)  5.2 (86)  5.2 (86)  5.2 (86)  6	Engine Model (Color)	E3RG4 Graphite
Displacement - cu in (cc) Gear Ratio 2.15:1  Full Throttle RPM Range Weight - lbs (kg)* Starting Controls Fuel Induction Steering Trim Method Shaft Length - in (mm) Oil Tank Capacity - fl oz (ml) Recommended Oil Recommended Fuel Warranty Emissions Compliance Warranty S-2003-6000 RPM  5.2 (86) 2.15:1  5.2 (86)  6.2	Engine Type	1-cylinder
Gear Ratio  Full Throttle RPM Range  Weight - Ibs (kg)*  Starting  Controls  Fuel Induction  Steering  Trim Method  Shaft Length - in (mm)  Oil Tank Capacity - fl oz (ml)  Recommended Oil  Recommended Fuel  Warranty  Emissions Compliance  Warranty  S000-6000 RPM  41 (18.4)  Cappe  Tiller Handle  Carbureted  Tiller  Manual  Manual  15 (381)  10 (300)  Evinrude/ Johnson 5W40 Ultra 4-Stroke Oil  87 Octane  Warranty  3-Year, Non-Declining  EPA 2013 / CARB 3 STAR  3-Year, Non-Declining	Bore x Stroke - in (mm)	2.17 x 1.42 (55 x 36)
Full Throttle RPM Range  Weight - Ibs (kg)*  Starting  Controls  Fuel Induction  Steering  Trim Method  Shaft Length - in (mm)  Oil Tank Capacity - fl oz (ml)  Recommended Oil  Recommended Fuel  Warranty  Emissions Compliance  Warranty  South (18.4)  All (18.4)  Rope  Carbureted  Carbureted  Tiller  Tiller  Manual  15 (381)  10 (300)  Evinrude/ Johnson 5W40 Ultra 4-Stroke Oil  87 Octane  Warranty  S-Year, Non-Declining  EPA 2013 / CARB 3 STAR  3-Year, Non-Declining	Displacement - cu in (cc)	5.2 (86)
Weight - Ibs (kg)*  Starting Rope Controls Tiller Handle Fuel Induction Steering Trim Method Shaft Length - in (mm) Oil Tank Capacity - fl oz (ml) Recommended Oil Recommended Fuel Warranty Shaft Length Warranty Steering Tiller Tiller Tour Manual Shaft Length - in (mm) Tour (300) Steven Sw40 Ultra 4-Stroke Oil	Gear Ratio	2.15:1
Starting Rope Controls Tiller Handle Fuel Induction Carbureted Steering Tiller Trim Method Manual Shaft Length - in (mm) 15 (381) Oil Tank Capacity - fl oz (ml) 10 (300) Recommended Oil Evinrude/ Johnson 5W40 Ultra 4-Stroke Oil Recommended Fuel 87 Octane Warranty 3-Year, Non-Declining Emissions Compliance EPA 2013 / CARB 3 STAR Warranty 3-Year, Non-Declining	Full Throttle RPM Range	5000-6000 RPM
Controls  Fuel Induction Steering Trim Method Shaft Length - in (mm) Oil Tank Capacity - fl oz (ml) Recommended Oil Recommended Fuel Warranty Shaft Length Shaft Length - in (mm) Oil Tank Capacity - fl oz (ml) Recommended Fuel Shaft Length - in (mm) Sha	Weight - lbs (kg)*	41 (18.4)
Fuel Induction Steering Trim Method Shaft Length - in (mm)  Oil Tank Capacity - fl oz (ml)  Recommended Oil Recommended Fuel Warranty Emissions Compliance Warranty Steering Tiller Manual Shaft Length - in (mm) 15 (381) 10 (300) Evinrude/ Johnson 5W40 Ultra 4-Stroke Oil 87 Octane 3-Year, Non-Declining EPA 2013 / CARB 3 STAR 3-Year, Non-Declining	Starting	Rope
Steering Trim Method Manual Shaft Length - in (mm) Dil Tank Capacity - fl oz (ml) Recommended Oil Recommended Fuel Warranty Emissions Compliance Warranty Tiller Manual 15 (381) 10 (300) Evinrude/ Johnson 5W40 Ultra 4-Stroke Oil 87 Octane 3-Year, Non-Declining EPA 2013 / CARB 3 STAR 3-Year, Non-Declining	Controls	Tiller Handle
Trim Method Shaft Length - in (mm)  Oil Tank Capacity - fl oz (ml)  Recommended Oil Recommended Fuel Warranty Emissions Compliance Warranty  Shaft Length - in (mm)  15 (381)  10 (300)  Evinrude/ Johnson 5W40 Ultra 4-Stroke Oil  87 Octane  3-Year, Non-Declining  EPA 2013 / CARB 3 STAR  3-Year, Non-Declining	Fuel Induction	Carbureted
Shaft Length - in (mm)  Oil Tank Capacity - fl oz (ml)  Recommended Oil  Recommended Fuel  Warranty  Emissions Compliance  Warranty  Shaft Length - in (mm)  15 (381)  10 (300)  Evinrude/ Johnson 5W40 Ultra 4-Stroke Oil  87 Octane  3-Year, Non-Declining  EPA 2013 / CARB 3 STAR  3-Year, Non-Declining	Steering	Tiller
Oil Tank Capacity - fl oz (ml)  Recommended Oil  Recommended Fuel  Warranty  Emissions Compliance  Warranty  S-Year, Non-Declining  EPA 2013 / CARB 3 STAR  Warranty  3-Year, Non-Declining	Trim Method	Manual
Recommended Oil Recommended Fuel Warranty Emissions Compliance Warranty Semissions Compliance Warranty Semissions Compliance Warranty Warranty Semissions Compliance Warranty Semissions Compliance Warranty Semissions Compliance Warranty Warranty Semissions Compliance Warranty Semissions Compliance Warranty Semissions Compliance Warranty Semissions Compliance Warranty	Shaft Length - in (mm)	15 (381)
Recommended Fuel 87 Octane Warranty 3-Year, Non-Declining Emissions Compliance EPA 2013 / CARB 3 STAR Warranty 3-Year, Non-Declining	Oil Tank Capacity - fl oz (ml)	10 (300)
Warranty 3-Year, Non-Declining Emissions Compliance EPA 2013 / CARB 3 STAR Warranty 3-Year, Non-Declining	Recommended Oil	Evinrude/ Johnson 5W40 Ultra 4-Stroke Oil
Emissions Compliance EPA 2013 / CARB 3 STAR Warranty 3-Year, Non-Declining	Recommended Fuel	87 Octane
Warranty 3-Year, Non-Declining	Warranty	3-Year, Non-Declining
	Emissions Compliance	EPA 2013 / CARB 3 STAR
Emissions Compliance EPA 2013 / CARB 3 STAR / European Union	Warranty	3-Year, Non-Declining
	Emissions Compliance	EPA 2013 / CARB 3 STAR / European Union



